

RB-RTU 30 READY TO USE FLEXIBLE TILE ADHESIVE



DESCRIPTION

Ready to use dispersion based adhesive for fixing tiles, insulation boards and decorative panels

APPLICATION FIELDS

It is used for bonding tile, ceramic, mosaic, decorative panels, thermal and acoustic insulation boards (Styrofoam, polyethylene hard foam etc.). It is applied to all indoor walls and ceilings, wet areas such as bathrooms and kitchens, old coatings. It can be applied on concrete, eternity, plaster ornament, sandwich type plaster boards, wooden and painted surfaces.

FEATURES

- Ready to use
- Resistant to damp
- Easy and rapid application
- High adhesion characteristic
- Flexible

TECHNICAL SPECIFICATIONS

- Bulk density: 1.5 kg/cm³
- Application temperature: 5-30 °C
- Adhesive tension strength:
Dry ≥ 1 N/mm²
Wet ≥ 0.5 N/mm²
- Color: White
- Temperature resistance: -20°C to 70°C
- Open time: Approx. 25 minutes
- Ready for mechanical stress: After 48 hours
- Shelf life: 12 months

DIRECTION FOR USE

RB-RTU 30 should be applied on an appropriately prepared surface by using a spatula and applied as wavy lines with the help of a notched trowel. That way equal layer thickness will be ensured. Panels or tiles are pressed on top of adhesive. A trowel with triangular tooth should be used when bonding tiles with flat back.

SAFETY

The surface or the material that will be bonded with RB-RTU 30 should be absorbent. Otherwise, should be considered that the drying time would be longer when bonding over old ceramic.

CONSUMPTION

Tooth depth (mm)	Consumption (kg/m ²)
3	1.7
4	2.0
6	2.7
8	3/3